



European XFEL Working Point Optimization and Status




W. Decking, T. Limberg (DESY)
for the European XFEL Team




European XFEL in Hamburg


2






Accelerator Consortium

3






- Normal conducting photo-cathode gun
- CsTe-Cathode, 60 MV/m gradient
- Peak power ~ 6 MW, Average ~ 100 kW
(2700 bunches with 10 Hz)
- In operation at FLASH and PITZ
- New best values for emittance achieved 2011
- Ongoing R&D on the drive laser to enhance flexibility and stability
- 'Laser Bouncer' in development







XFEL – New Parameter Set

5




	Baseline	New Parameter Set
Electron Energy	17.5 GeV	10.5/14/17.5 GeV
Bunch charge	1 nC	0.02 - 1 nC
Peak current	5 kA	5 kA
Slice emittance	< 1.4 mm mrad	0.4 - 1.0 mm mrad
Slice energy spread	1.5 MeV	4 - 2 MeV
Shortest SASE wavelength	0.1 nm	0.05 nm
Pulse repetition rate	10 Hz	10 Hz
Bunches per pulse	3000	2700




Injector schematic layout





Level 7 of injector building



- Laser heater mechanical design matured, first components tendered




- Low remanence focusing quadrupoles produced
- Prototype of transverse deflecting structure produced, to be installed at PITZ
- 3.9 GHz accelerator module (for bunch length control), design finished, prototype cavities in test



17.5 GeV Linac

8


100 accelerator
modules



800 accelerating cavities
1.3 GHz / **23.6** MV/m




25 RF stations
5.2 MW each




Bunch Compression


9



3 stage bunch compression for wide range of compression scenarios and minimized sensitivities to RF-regulation imperfections and electron beam driven instabilities




Bunch Compression Chicanes





- Fixed wide vacuum chamber for variable R56
 - No moving vacuum parts in the vicinity of superconducting structure
 - No wake from bellows
 - Fast changes of R56 via beam energy


- First dipole magnets for the chicane produced
 - Challenging field quality requirements will be achieved by individual pole shimming



Calculation of BC Working Points: Criteria and Constraints



Calculation of BC Working Points



■ total compression to stage n : $C_n(s) = \left(\frac{d}{ds} S_n(s) \right)^{-1}$ With: s = initial long. Position and s_n = long. position after stage n


■ two stage compression:

$$\underbrace{\left\{ \begin{array}{l} \text{BC energies} \\ \text{compression factors} \\ \text{higher derivatives} \end{array} \right\} \begin{pmatrix} E_0 \\ E_1 \\ C_0 \\ C_1 \\ C'_1 \\ C''_1 \end{pmatrix}}_{\text{working point parameters (y)}} = f \left(\underbrace{A_0, \varphi_0, A_0^{(h)}, \varphi_0^{(h)}, A_1, \varphi_1}_{\text{LINAC parameters (x): amplitudes and phases}}, \underbrace{\psi_0, \psi_1}_{\text{compressor parameters (p): magnet strengths or } R_{56}} \right)$$


$$\mathbf{y} = f(\mathbf{x}, \mathbf{p})$$

For a simplified model, inverse function can be calculated: $\mathbf{x} = g(\mathbf{y}, \mathbf{p})$



Longitudinal Bunch Profile Parameterization



higher derivatives of total compression are used to specify bunch shape




C' bunch center and symmetry




C'' bunch tails


Example: XFEL – BC working point vs. rf Sensitivity



Sensitivity L0



RMS Sensitivity (rf system)



$$S_0 = 120$$

$$\left| \frac{\Delta C}{C} \right| < 0.1 \rightarrow \left| \frac{\Delta A_0}{A_0} \right| < \frac{0.1}{120} \approx 0.00083$$

Micro-Bunching Instability Gain Curves

15

integral equation method:

$$G = \frac{\tilde{I}(z)}{I(z)} \frac{I(0)}{\tilde{I}(0)}$$

gain factor, amplification of **relative** modulation

 z = length along linac λ_i = wavelength of initial density modulation


K = kernel depends on **impedance**, current, optics, rf settings,
spectrum of uncorrelated **energy spread**, ...

Heifets, Stupakov: PhysRev ST, 064401 2002


Huang, Kim: PhysRev ST, 074401 2002

laser heater


example:
E-XFEL




Micro-Bunching Instability Gain




max-max gain, LH → 1MeV (compressed)



max-max gain, LH → 2MeV (compressed)




$$S_{\text{rms}} = \sqrt{\sum S_n^2}$$



European XFEL Working Point for 1 nC, 5 kA, Total Compression Factor: 100

■ three stage compression (E-XFEL)




■ BC energies: pre defined


■ compression factors: **free**, but total compression fixed (=100)

■ higher derivatives of total compression: pre defined


■ compression parameter: R56, from rf stability and micro-bunching gain optimization, constraints from RF, BC, maximal ΔE




High Level Simulation




Full 3D simulation method (200 CPU, ~10 hours)



Iterative Process to find Working Point



Full 3D simulation method (200 CPU, ~10 hours)



$$\mathbf{y}_n = f_Q(\mathbf{x}_n, \mathbf{p}, Q)$$

3D model


1D model

$$\mathbf{x}_{n+1} = g\left(\mathbf{y} - \mathbf{y}_n + f(\mathbf{x}_n, \mathbf{p}), \mathbf{p}\right)$$

↑
(use low level inverse function)


I.Zagorodnov, M.Dohlus: A Semi-Analytical Modeling of Multistage
Bunch Compression with Collective Effects, Phys. Rev. STAB, 2011.

European XFEL BC Exit: 1 nC, 5 kA, Total Compression Factor: 100




δ_E

Phase space



bunch head

Current, emittance, energy spread





$$\epsilon_x^{proj} = 0.9 [\mu\text{m}]$$

$$\epsilon_y^{proj} = 3.5 [\mu\text{m}]$$

$$Q = 20 \text{ pC}$$

XFEL beam dynamic simulations for different charges (full)



$$Q=20 \text{ pC}$$



$$\epsilon_x^{proj} = 0.14 [\mu\text{m}]$$




$$\epsilon_y^{proj} = 0.26 [\mu\text{m}]$$

Fast Model for longitudinal Phase Space






- Further understanding of the physics high density electron bunches; comparison of detailed phase space measurements at FLASH with simulations

LOLA measurement:






calculation with self effects:



Beam Based Feedbacks for control of longitudinal parameters

- Measurements of beam arrival time (BAM) and bunch compression (BCM) feedback on RF parameters
- Concept implemented and tested at FLASH (intra-train arrival time and slow 5x5)




Beam Diagnostics

25





Coherent Radiation Diagnostics
(peak current)


Current Monitor



Dark Current Monitor
(also very sensitive
charge monitor)




Beam Arrival Time Monitor



Beam Position Monitor

Collimation & Beam Distribution


26





- Collimation system for beam halo cleaning and emergency beam stop
- Transvers Intra-Bunch Feedback
- Flexible beam distribution system for quasi-simultaneous operation of two primary electron beam lines

- Downstream equipment protection: survival of direct hit of up to 100 bunches
- Collimation of up to 12 kW average power in beam halo (over short time)
- 50 cm long collimator blocks with different radii (2mm smallest)

XFEL Collimator





- Development of ultra-stable flat-top pulser
- Pre-Series production 2012




- Design of septum magnet

Stability measurements at FLASH




- Design of vacuum system

Beam Distribution Shaft – XS1




Beam Distribution Shaft – XS1



Simultaneous operation of many instruments

31

- Within the bunchtrain
 - 2 e⁻ beamlines
 - 5(+) undulators
 - 15(+) instruments



Boxes only placeholders !

Sophisticated electron bunch distribution


- 27.000 bunches/sec to 5 beamlines
- in average 10-20 Hz and ~500 pulses/train
- using kicking methods to make bunches lase only in dedicated undulator

Electron bunch distribution to 2 BL / 5 undulators


32

- e-beam distribution to 2 beamlines


- Slots for feedback & switching
- Equal splitting on both e-BL



- Equal splitting on 3 undulators




- Equal splitting on 5 und. (future)



- Asymmetric splitting




- Specific electron bunch properties




Pulse Distribution

33




- low accuracy (>1 %)
- 4.5 MHz burst operation





example:
pulser prototype measurement

- high accuracy (< 0.01 %)
- 10 Hz operation




example:
pulser prototype measurement

Energy Variation – Within Pulse




$$\Delta E/E_{\text{max}} = 3 \%$$




$$\Delta E/E = + 10^{-4} / \mu\text{s} \\ - 10^{-3} / \mu\text{s}$$

Multiple – gradient/phase operation






■ Preparation of software for FLASH 1 & 2 & 3 operation!



- Used gradient steps -2% and + 3% with 40 μs transient time
- Set-up time < 10 sec

European XFEL – Undulators


36



Pre-series arrived & measured, series ordered (total 35+35+22)

Beam Dumps


37



Production readiness reviews for all beam dumps finished

- Construction, infrastructure planning and ramp up of accelerator component fabrication on track
- Working hard to finish installation in time for
 - start of injector commissioning mid 2014
 - start of linac commissioning mid 2015
 - observe first SASE by end of 2015


Overview XFEL Accelerator Schedule 17.5 GeV




Thank you for your attention!




Repetition Rate Variation Limits



- cryo-losses: $P_{loss} \approx N_{modules}(P_{static} + c f_{rep} T_{total} V_{acc}^2) < 2 \text{ kW for all,}$
 $< 30 \text{ W single module}$
- rf system: $P_{kly,peak} \approx \frac{N_{bunches} C_{bunch}}{T_{pulse}} V_{acc} \#_{modules} f_{reg} < 10 \text{ MW}$
 $P_{kly,ave} \approx P_{kly,peak} f_{rep} T_{total} < 150 \text{ kW}$
- dump: $P_{beam} = f_{rep} N_{bunches} C_{bunch} E_{beam} < 300 \text{ kW}$




Design of the main dump. (City 5)



Repetition rate variations

41



Gun limit

CW or Near CW Operation

42

- From dump

$$P_{beam} = f_{rep} N_{bunches} C_{bunch} E_{beam} < 300 \text{ kW}$$

- From Cryo-plant

$$P_{loss} \approx \#_{modules} (P_{static} + c f_{rep} T_{total} V_{acc}^2) < 2 \text{ kW}$$

- From new IOT (inductive output tube) based RF system

$$P_{kly} \approx \frac{N_{bunches} C_{bunch}}{T_{total}} V_{acc} \#_{modules} f_{reg} < 120 \text{ kW}$$

ACCELERATORS | PHOTON SCIENCE | PARTICLE PHYSICS

Deutsches Elektronen-Synchrotron
A Research Centre of the Helmholtz AssociationURL: <http://www.desy.de/news/@@news-view>


13.07.2011

The first continuous wave and long-pulse operation of the XFEL-type cryomodule

Continuous wave (CW) and long-pulse (LP) operation modes of the XFEL superconducting linac are an attractive future option to enhance the experimental potential of this European facility, being currently under construction. On Wednesday 7 July 2011, a two-week test was finished in which the XFEL-type cryomodule, a building block of the XFEL linac, for the first time was operated successfully in both, CW and LP mode with accelerating gradients up to 5.5 MV/m and 11.5 MV/m, respectively.





Beam Diagnostics: Screens and Wires



Beam Size Measurements

- ~ 50 Screens
- 12 Wire scanners



- 2nd design iteration for wire scanners
- Issue with Coherent OTR from compressed bunches:
 - gated camera
 - spatial separation
- Screen material tests at MAMI performed

