



# GSI UNILAC Preparation and the New Proton Linac for FAIR Operations



L. Groening, R. Brodhage, O.K. Kester, A. Adonin, X. Du, R. Hollinger, S. Mickat, A. Orzhekhevskaya, B. Schlitt, G. Schreiber, H. Vormann, C. Xiao  
GSI/Germany

H. Hähnel, U. Ratzinger, A. Seibel, R. Tiede,  
Goethe University of Frankfurt/Germany

- The FAIR Project
- UNIversal Linear ACcelerator UNILAC
- Proton Linac

# FAIR Facility for Antiproton and Ion Research



Nuclear Structure & Astrophysics  
(Rare-isotope beams)


Hadron Physics  
(Stored and cooled  
14 GeV/c anti-protons)

QCD-Phase Diagram  
(HI beams 2 to 45 GeV/u)

Fundamental Symmetries  
& Ultra-High EM Fields  
(Antiprotons & highly stripped ions)

Dense Bulk Plasmas  
(Ion-beam bunch compression  
& petawatt-laser)

Materials Science & Radiation Biology  
(Ion & antiproton beams)



courtesy B. Sharkov

GSI

# FAIR Facility for Antiproton and Ion Research



## Primary Beams SIS 100


- $2 \times 10^{11}$  U<sup>28+</sup> ions/s; 1.5 GeV/u
- $10^{10}/s$  <sup>238</sup>U<sup>92+</sup> up to 11 GeV/u
- $2 \times 10^{12}$  protons/s; 29 GeV

## Secondary Beams

- range of radioactive ion beams up to 1.5 - 2 GeV/u; up to a factor of 10'000 higher in intensity than presently
- antiprotons 1.5 - 14.1 GeV

## Storage and Cooler Rings

- radioactive ion beams
- antiproton beams:
  - CR:  $10^8$  antiprotons; 3 GeV
  - HESR:  $10^{10}$  antiprotons; 1.5 - 14.1 GeV








## Technical Challenges

- Rapid cycling superconducting magnets
- rf-systems and control
- Beam lifetime (dynamic vacuum)
- Cooled beams

# Status of FAIR Accelerators

talk TUBB2 this afternoon





Title	Poster ID
pulsed quadrupoles	WEPMA021
SIS100 dipoles	WEPMA020
high energy beam transp. system	THPF012
status SIS100	THPF015
heavy ion induced absorption	THPF010
cryogenic surfaces in SIS100	THPF009

# UNIversal Linear ACcelerator UNILAC




design parameters

ion A/q	$\leq 8.5$ , i.e. $^{238}\text{U}^{28+}$	
beam current (pulse) * q/A	1.76 (0.5% duty cycle)	emA
input beam energy	1.4	MeV/u
output beam energy	11.4	MeV/u
normalized total output emittance, horizontal/vertical	0.8 / 2.5	mm mrad
beam pulse duration	$\leq 5000$	$\mu\text{s}$
beam repetition rate	$\leq 50$	Hz
operating frequency	108.408	MHz
length	$\approx 100$	m



# UNILAC: Available Beams




beam time schedule April 2012

2013-2014 saw considerable maintenance works



## UNILAC: Achieved Currents

- June 2007: current of 6.0 mA  $^{238}\text{U}^{27+}$  at the entrance to SIS18 was achieved



- Nov 2014: current of 7.7 mA within 1.5 mm mrad  $^{238}\text{U}^{28+}$  at stripper section was achieved
- although UNILAC did not achieve yet the target value of 15 mA, this machine keeps holding the uranium intensity world record and might do so for many years

# UNILAC Upgrade: Dedicated Uranium Source & LEBT




NIM A 788 173 (2015)

- new „Terminal West“ under design
- will provide exclusively  $^{238}\text{U}$
- improved (compact) extraction system
- LEBT is w/o bends (hex-pole fringes, dispersion)
- no dispersive separation of charge states ( $3^+, 4^+$ )
- just chromatic separation (envelopes + irises)
- compromise between:
  - vast ion species portfolio
  - safety issues wrt uranium operation/handling


# UNILAC Upgrade: Pulsed H<sub>2</sub>-Stripper: U<sup>4+</sup>→U<sup>28+</sup>




present



- continuous jet
- nitrogen
- 4 bar





new



- pulsed jet ( $\approx$  ms)
- light gases (H<sub>2</sub>, He, ...)
- pressure  $\gtrsim$  100 bar

increased stripping efficiency to q=28+



# Linac Emittances vs effective Ring Acceptances




- “round” beam is provided by **injector linac**





$$\epsilon_x \approx \epsilon_y$$

- flat beams might be required by **rings** (MTI)

$$A_x < A_y$$



# UNILAC Upgrade: Provision of Flat Ion Beams (optional), Proof of Principle EmTEx






# UNILAC Upgrade: New Alvarez Cavities



- improved shapes of drift tube end plates
- optimization of shunt impedance per surface field
- „freehand-shape“
- manufacturers:
  - „freehand-shape is no considerable cost driver“
  - feasible at same tolerances as const-R-shapes
- beta profile of tank I (new wrt present)
  - same length & energy gain but 18% less rf-power (unloaded)
  - 8% higher surface field

	tank I	tank II	tank III	tank IV
energy range [MeV/u]	1.39 – 3.56	3.56 – 5.69		- 11.4
# cells	61	40		
$L_{\text{gap}} / L_{\text{cell}}$	0.26 – 0.27	0.24 – 0.25		
rf-length [m]	12.2	11.0		
$E_{\text{surf,max}} [E_K]$	1.03	1.03		1.03
$P_{\text{loss,MWS}} [\text{MW}]$	0.92	0.94		
$P_{\text{beam}} [\text{MW}]$	0.28	0.27		
$\langle Z_{\text{eff}} \rangle [\text{M}\Omega/\text{m}]$	15.2	15.9		






# UNILAC Upgrade: DTL Cavity Stem Orientations



each drift tube is kept by two stems (as today):

- facilitates provision of quad current and water cooling of tubes & quads
- well-considered orientations of stems mitigate parasitic TM rf-modes

robustness of field flatness wrt  
perturbations of inter drift tube  
capacities




- 1:3 scaled cold model under production to probe experimentally:
- different stem orientations
  - different drift tube shapes

# UNILAC Upgrade: Stronger Transverse Focusing



- today transv phase advance is limited to  $\sigma_0 = 53^\circ$  (zero current) with  $^{238}\text{U}^{28+}$
- too low in order to avoid parametric resonances (Hofmann's stability chart)





- to improve position in stability chart, move:
  - upwards: do emittance transfer while keeping 4d-emittance
  - left: increase transverse focusing strength  $\sigma_0 \rightarrow 67^\circ$


# UNILAC Upgrade: Asymmetric Transverse Focusing (optional)



- focusing shall preserve beam emittance ratio (flatness)
- space charge drives re-equilibration of emittances
- can be mitigated by stronger focusing in ver plane
- ver focusing quads with stronger gradients wrt hor ones
- few % of increase of ver quad gradients is sufficient



# UNILAC Upgrade: Estimate of attainable $^{238}\text{U}^{28+}$ Performance, Schedule





2014/15	concepts
2015	prototyping conceptual design
2016/17	final design
2017/18	tendering
2018/19	fabrication
2020	assembly
2021	commissioning

beamline section	current change factor	rel. emit. growth [%]	brilliance change factor	current [mA]	hor. emittance (norm., tot.90%)	upgrade activity
LEBT + RFQ	0,9	15	0,78	18,0	0,38	source development
MEBT + IH-DTL	0,9	70	0,53	16,2	0,44	RFQ upgrade
gaseous stripper (to A1)	1,26	15	1,10	14,6	0,74	new MEBT
EmTEx	0,9	-60	2,25	18,4	0,85	routine operation pulsed stripper
Alv-DTL, transf. to SIS18	0,85	50	0,57	16,5	0,34	installation
<b>target value</b>				<b>14,1</b>	<b>0,51</b>	<b>new DTL</b>
				<b>15,0</b>	<b>0,56</b>	

# FAIR Proton Linac

design parameters

Beam Energy (MeV)	70
Design Current (mA)	70
Beam Pulse Length ( $\mu$ s)	36
Repetition Rate (Hz)	4
Frequency (MHz)	325.224
Norm. Emittance ( $\mu$ m)	4.2
Beam Loading (peak) (MW)	4.9
RF Power (peak) (MW)	2.2
# of Klystrons (3 MW Peak Power)	7
# of Solid State Amplifiers (45 kW)	3
Total Length	$\approx 27$ m





# Proton Linac: Source & LEBT



Beam Intensity (mA)	100
Beam Energy (keV)	95
Proton Fraction (%)	> 85


- designed, built, and to be commissioned at CEA/Saclay
- source is assembled
- solenoids and diagnostics chamber assembled
- chopper is under construction
- power supplies are ordered
- beam commissioning of LEBT with beam planned in Q1/2016
- installation of control system is ongoing



simulation of beam extraction

Poster  
WEPWA002


# Proton Linac: Cavities



- CH prototype cavity at GSI since end of 2013
- issues concerning Cu-plating investigated and solved
- low level-rf measurements started
- high power tests after klystron is prepared



**EB-welding tests**




# Proton Linac: Rf-Power Sources



- CERN modulator arrived and is under operation
- 2.5 MW power from klystron achieved
- GSI modulator design is under preparation based on the CERN layout
- 45kW amplifier for the buncher successfully tested on resonant load

Poster  
WEPMA022





# Proton Linac: Beam Instrumentation





combined BPM & phase probe  
(CEA/Saclay, TU-Darmstadt, GSI)

$$\Delta\Phi = 1^\circ$$

$$\Delta x = 0.1 \text{ mm}$$



non-intercepting bunch  
shape monitor  
(INR Moscow, GSI)



# Summary

- FAIR Accelerators
  - R&D finished
  - status: writing specs, tendering, testing
  - all machines commissioned in 2022
- UNILAC Upgrade:
  - dedicated uranium LEBT
  - increase of stripping efficiency using pulsed H<sub>2</sub> jet  $\geq$  150 bar
  - completely new post stripper Alvarez DTL
    - provision of hor flat beams for MTI optimization (optional)
    - optimized DT shape wrt shunt impedance per surface field
    - varying stem orientations for parasitic mode damping
    - increase of transv focusing to avoid space charge driven resonances
  - upgrade finished in 2020
- Proton Linac
  - prototyping of crossed-bar H-cavities almost finished
  - first MW-Klystron power in 2015
  - new development of combined BPMs & phase probes
  - missing components will be tendered before summer 2016
  - commissioning in 2020



# Thank you !