

FLS23 / Luzern, CH / 2023-08-28

FLASH: Status & Upgrade. (MO3A5)

Mathias Vogt (DESY/MFL)

Deutsches Elektronen-Synchrotron DESY, Hamburg, Germany, EU

for my co-authors:

S.Schreiber, J.Zemella


and for the complete FLASH- & FLASH2020+ -teams!



Content.


- **FLASH**
- **FLASH2020+**
- **The 2021/22 Shutdown**
 - Injector Upgrade (FLASH0)
 - Laser Heater
 - BC2
 - partial compensation of long.-transv. correlations
 - minor **FLASH2** changes
- **The 2024/25 Shutdown ... a Staged Approach**
 - **FLASH1** : external seeding + ...
 - μ Bunching studies for seeding
 - stage-FULL vs. stage-0
- **Summary / Outlook**

FLASH pre FLASH2020+.




- superconducting free-electron laser
w/ 2 FEL beamlines run simultaneously → for FEL user experiments
 - exclusively: **FLASH2** ↔ **FLASH3**
 - **FLASH3**: plasma wake field acc. experi.
FLASHForward>>
- injector/linac → **FLASH0**
→ switch-yard to
 - **FLASH1**
 - **FLASH2**

FLASH0 pre FLASH2020+.




- injector/linac :
→ photo cathode RF gun \sim 600 bu 1 MHz
 $\times 10$ Hz
- 1st TESLA-type L-band module (**ACC1**):
- SC 3.9 GHz linearizer
(4 scaled TESLA cav.s) (**ACC39**)
- NC 3.0 GHz long. feedback cavity
(**BACCA**)
- 1st bunch compr. chicane
(*now called FL0BC1*)
- 2nd & 3rd TESLA-type L-band module
(**ACC2 & ACC3**)
- 2nd bunch compr. chicane
(*now called FL0BC2*)
- “main linac” 4 \times (TESLA) L-band
modules (**ACC4/5/6/7**)

FLASH1 pre FLASH2020+.



- E -collimation dogleg
- seeding experiment **Xseed**
- NC 2.865 GHz transverse deflecting structure (**LOLA**) from SLAC
← longitudinal diagnostics
- main SASE (Self Amplification of Stimulated Emission) undulator ← *fixed gap* :-(
- spent beam THz undulator (pump-probe experiments)
- tilted (x/y -coupled) dump line :-(

FLASH2 & FLASH3 pre FLASH2020+.




- switch-yard (_{FLASH0}): kicker/septum w/ Lambertson (DC) septum
- complicated extraction arc (geometry!!!)
→ also extraction to **FLASH3**
- **FLASH2's own** post-acceleration, post-extraction bunch compressor (**FL2BC**)
- optics matching
- 12× planar variable gap undu.: SASE + advanced extensions: (harmonic-lasing-self-seeding, frequency doubler, etc.)
- 12.0 GHz PolariX TDS
- electron-photon separation + uncoupled dump line

FLASH2020+ : Motivation.

- FLASH ([SRF= high rep-rate] + soft X-ray + SASE)×2 beamlines should stay competitive for the next 10-20 years
 1. make lower photon wavelengths possible (“water window”)
⇒ increase beam energy & afterburner-undulators
← but keep the footprint!
 2. variable photon polarization ⇒ helical APPLE-III undulators
 - 3.a increase longitudinal photon pulse coherence ⇐ external seeding (HGHG/EEHG)
 - 3.b but keep THz output (⇐ pump-probe) → post compressor
 4. high quality beams require improved...
 - ... operability: transverse matching & reduce long.-2-transv. intra-bunch-corr.s & long. PS-diagnostics
 - ... better stability: ameliorate μ Bunching & remove intra-train orbit slopes


FLASH after the 2021/22 Shutdown.



- 2021/22: changes:
only in **FLASH0** & **FLASH2**
- **FLASH0:** upgrade towards:
 - better beam quality/stability
 - higher final energy

- **FLASH2:** upgrade towards:
 - variable photon polarization
 - enhanced 3rd harmonics
 - ← APPLE-III undulator
 - ← prototype for
FLASH1 seed radiators


FLASH0 after the 2021/22 Shutdown.



- new injector laser system prepared
- new laser heater installed → space!
⇒ BC1 shifted downstream ← space!
- ⇒ matching section shrunk & modified to fulfill requirements
- ACC2 & ACC3:
new **high gradient** modules

- redesign of FL0BC2:
S-type → C-type
→ gain space for improved matching
- round chamber → quad/BPM/
skew-quad packs *possible*
- movable chamber (+ inner dipoles)
→ keep variability for simultaneously seeding (**FL1**) and SASE (**FL2**)


The FLASH0 Laser Heater.



- (**LEFT**): incoupling chicane for LH laser
- overlap bunch w/ laser (green) in undulator (**RIGHT**)
- 1st BC-chicane (FL0BC1): strongly over-folds E -modulation
- Increased slice E -spread reduces the μ Bunching gain (+)
but it also reduces the FEL gain (-)
⇒ very sensitive knob for tuning
- Commissioning: overlap achieved & μ Bunching killed & SASE killed
but the sophisticated stuff is still coming!



FL0BC2.

- replace old 6-dipole S-type chicane by new 4-dipole C-type chicane
⇒ gain some space for matching
- round vacuum chamber allows quad/BPM/skew-quad pack
around the chamber
⇒ partial compensation of *systematic* longitudinal-to-transverse correlations
inside the bunches
- ⇐ bunch has E -chirp, chicane has hor. dispersion
→ head sees different kick through quad/skew-quad than tail
- movable chamber and the inner dipoles to enable change of deflection angle




Compensating Long.-Transv. Correlation w/ FL0BC2.

- Idea by Guetg, Beutner, Prat, Reiche; Decker, Ding, Huang, Maxwell; (2015/16)
- $\langle \eta \rangle_{\perp}(\tau) := \int_{\mathbb{R}^5} \eta \Psi(\vec{z}_{\perp}, \eta, \tau) d^4 z_{\perp} d\eta$
 $\Rightarrow \langle \eta \rangle_{\perp}(\tau) = h\tau + O(\tau^2)$
 \leftarrow bunch compression
- $\langle \vec{z}_{\perp} \rangle_{\perp}(\tau) := \int_{\mathbb{R}^5} \vec{z}_{\perp} \Psi(\vec{z}_{\perp}, \eta, \tau) d^4 z_{\perp} d\eta$
 $\Rightarrow \boxed{\langle \vec{z}_{\perp} \rangle_{\perp}(\tau) = \vec{\xi}\tau + O(\tau^2)}$
- long.-to-transv. correlation
 \leftarrow compensate in chicane




- thin lens model (IPAC21/TUPAB102)
- solve exactly for $\delta = 0$,
 then solve $O(\delta)$ f. $\delta > 0$
- gives quad/skew quad strengths
 for given correlation and E -chirp
 comes at a prize: disp_{\perp} leaks & M_{56} modified

The Energy Upgrade.




- pics: FLASH0
 - w/o old ACC2 & ACC3 in Jan. 2022 (left)
 - ← the weakest modules in FLASH: beam energy at 2nd BC **was 450 MeV**
 - w/ the new ACC3 already placed on supports Feb. 2022 (right)
- replaced by **refurbished, XFEL-type modules PXM2.1 and PXM3.1**
- cav's new ACC2 : from 29MeV/m to 34MeV/m; cav's new ACC3 : from 24MeV/m to 34MeV/m
 - + optimized power distribution through ACC23 wave guides
- ⇒ E -gain of > 417 MeV possible even 25° off-crest
- great success: Beam energy at 2nd BC immediately up to 550 MeV, recently even **560 MeV** ⇒ E -upgrade save to > 1300 MeV

FLASH2 after the 2021/22 Shutdown.



- last undulator ex-FL2SASE14 moved to FL2SASE2 (ex-FL2SEED7)
- space for afterburner undulator in ex-FL2SASE14 (now FL2BURN)
 - beam diagnostics shifted upstream & shorter
 - new matching into undulator
- APPLE-III 3rd harmonic a-burner
 - ⇒ down to 1.3 nm
 - & variable photon polarization
- **6 mm diameter** chamber already installed in FL2BURN
- parts for APPLE-III delayed:
installation end of September?

FLASH after the 2024/25 Shutdown : Stage-FULL.






- 2024/25: only **FLASH1**
- the old **FLASH1** will be completely removed → disentangle photon beamline from dump line
- **FLASH1**: upgrade towards:
 - HGHG/EEHG seeding
 - variable polarization (helical APPLE-III undulators)
- 4 new chicanes: 3 for seeding & 1 as post-compressor for THz

EEHG Seeding at Xseed Experiment in FLASH1.

A major success: EEHG at FLASH


Worldwide unique: parallel operation of EEHG and SASE

- Initial EEHG setup looking at 12th harmonic took 3 full days!
 - Characterizing 12th harmonic
- Complete re-setup in only 4 hours
 - Characterizing harmonics 9, 12, 15 and 17
- Successful seeding of 2nd bunch
 - mimicking bunchtrain operation → full train to come
- Parallel SASE operation at FLASH2 with 30 bunches above 100uJ at 30 nm
- A major team effort!**
 - Expertise vital for future seeded FLASH1
- Continued experiments offer unique chance
 - Shorten commissioning time
 - Develop tools and procedures




μ Bunching Simulations using SelaV_{1D}.

- LSC(+CSR) induced μ bunching
- potentially degrades FEL performance
 - not always:
→ SpaceChargeAmplifier!!!
 - known to be more severe for external seeding
- **gain** mechanism well studied
(Stupakov; Venturini; Shneidmiller, Saldin; Amstutz; ...)
- **seed** mechanism mostly unclear → one thing is **shot noise**
- MP sim.: overestimating the intrinsic shot-noise
→ massive one-to-one simulations (extremely t -consuming!), **or**:
- SelaV_{1D}, based on backward tracking the PSD on **tree-grid** covering only the **support** of PSD
 - semi-Lagrangian tracking / Method of Characteristics /Perron Frobenius Operators
 - ⇒ w/ optimized compression WP and moderate LH amplitude → negligible




FLASH1 after the 2024/25 Shutdown : Stage-FULL.



- incoupling of seed laser **L1**
- 1st modulator
- over-folding chicane
(+ out-coupling **L1** + incoupling **L2**)
- 2nd modulator
- bunching chicane (+ out-coupling **L2**)
- seed radiators:
variable polarization APPLE-III
- new location of LOLA
- quasi-DBA (5°) & post-compressor
chicane & THz radiator
- new dump line
- **but then... the staged approach...**


FLASH1 FL1RADI Stage-FULL (top) vs. Stage-0 (bott.).




- 6 instead of 11 APPLE-III undulators
 - replace 3 of 5 w/ Xseed, P2N-type undulators as bunchers
 - leave 2 of 5 empty
(FODO-layout is kept)
 - No wire scanners / only WS-chambers
 - otherwise : intersections stay as designed

FLASH1 FL1PARC Stage-FULL (top) vs. Stage-0 (bott.).

FL1RADT
240.911 m



FL1RADT
240.947 m



- only OTR station for LOLA
- **No post-compression chicane FL1CH4**
- **i.e. No post-compression for THz undulator**
- x -dispersion from messing with quasi-DBA \Rightarrow parasitic use = **bunch length only** (full long. PS only in destructive mode)

Summary & Outlook.

- FLASH is undergoing a substantial upgrade/refurbishment program (**FLASH2020+**).
- **If we're quick**, then FLASH will be the only seeded soft X-ray FEL capable of ~ 5000 bu/sec.
- 1st upgrade shutdown (2021/22) went well:
user-run after quick beam commissioning.
→ Commissioning still ongoing whenever there's time. . .
- *E*-upgrade: two new very nice high-gradient modules for ACC2&3
 \Rightarrow 100-110 MeV more at end of the injector (FL0BC2)
- 2nd upgrade shutdown being prepared. Everything within schedule.
- However, in 2024/25 only reduced version possible = “stage-0”.
- Full upgradability to “stage-FULL” is guaranteed by design of stage-0.
- Seeded operation still uncompromised goal of stage-0.
- We are looking forward to the shutdown in 2024/25!

Thank you for Listening!