

Status of the Spallation Neutron Source: Machine and Science

**Stuart Henderson
*Oak Ridge National Laboratory***

***PAC 2007
June 25, 2007***



The Spallation Neutron Source


- The SNS at Oak Ridge National Laboratory is a short-pulse neutron source, powered by a 1.4 MW proton accelerator
- At 1.4 MW it will be ~8x ISIS beam power, the world's leading pulsed spallation source
- The SNS construction project, a collaboration of six US DOE labs, began in 1999 and was completed on-time and within budget in June 2006 at a cost of 1.4 B\$
- SNS began formal operation in October 2006, and now routinely provides neutron beams to three scattering instruments
- SNS will become the world's leading facility for neutron scattering




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007




Why Neutrons?




1. Neutrons have the right wavelength
Neutrons probe a broad range of length scales



2. Neutrons measure the velocity of atoms
Neutrons follow catalysts in action; transport through biological membranes



3. Neutrons see the nuclei
Can offer greater contrast than x-rays (e.g. H); isotopic contrasting



4. Neutrons see light atoms next to heavy ones
Crucial Oxygen positions in Hi-Tc superconductors; neutrons see H; study H-bonds (chemistry and biology)



5. Neutrons penetrate deep into matter
Study material properties deep inside materials; characterizing deep welds and their associated stresses



6. Neutrons see elementary magnets
Study magnetic structure of materials; advanced magnetic materials




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



The Beam Power Frontier for Protons

- Central challenge at the beam power frontier is controlling beam loss to minimize activation
- 1 nA protons at 1 GeV, a 1 Watt beam, activates stainless steel to 80 mrem/hr at 1 ft after 4 hrs
- Demands careful control of beam injection/extraction



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY

PAC 2007, June 25, 2007




SNS Accelerator Complex


Front-End:
Produce a 1-msec
long, chopped,
H- beam

**1 GeV
LINAC**


Accumulator Ring:
Compress 1 msec
long pulse to 700
nsec



SNS Beam Commissioning



- First Beam on Target, First Neutrons and Technical Project Completion goals were met April 28, 2006
 - 10^{13} protons delivered to the target
 - Neutron flux goals exceeded
- The SNS Construction Project was formally Completed in June 2006



Spallation celebration



Lab scientists, engineers, instrument specialists and others gather moments before the first neutrons were produced Friday at the \$1.4 billion Spallation Neutron Source facility.

Neutron source's test drive paves the way for research



One of several diagnostic screens shows the successful delivery of protons to a mercury target, producing neutrons for scientific research of materials.




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007




SNS Linear Accelerator




- Front-end was designed and built by Lawrence Berkeley National Laboratory
- Multicusp Cs-enhanced volume production H⁻ ion source



SNS Linear Accelerator




- Front-end was designed and built by Lawrence Berkeley National Laboratory
- Multicusp Cs-enhanced volume production H⁻ ion source
- Electrostatic LEBT (Low-energy beam transport)
- Chopping of 65 keV beam in LEBT and 2.5 MeV beam in MEBT




SNS Linear Accelerator



- Front-end was designed and built by Lawrence Berkeley National Laboratory
- Multicusp Cs-enhanced volume production H⁻ ion source
- Electrostatic LEBT (Low-energy beam transport)
- Chopping of 65 keV beam in LEBT and 2.5 MeV beam in MEBT
- 402.5 MHz RFQ with 2.5 MeV output energy
- Front-end design parameters:
 - 38 mA peak current
 - 68% beam-on chopping
 - 1.0 msec, 60 Hz, 6% duty
 - 1.6 mA average current



SNS Linear Accelerator




- SNS linac is the world's highest energy proton/H⁻ linac
 - Achieved 1.01 GeV in a demonstration run
- SNS linac architecture consists of
 - Conventional normal conducting structures to 186 MeV
 - Superconducting structures to 1 GeV



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



SNS Linear Accelerator



- SNS linac is the world's highest energy proton/H⁻ linac
 - Achieved 1.01 GeV in a demonstration run
- SNS linac architecture consists of
 - Conventional normal conducting structures to 186 MeV
 - Superconducting structures to 1 GeV
- Normal conducting linac was designed and built by Los Alamos National Laboratory
- DTL system consists of 6-tanks, each powered by 2.5 MW, 402.5 MHz klystron



SNS Linear Accelerator



- SNS linac is the world's highest energy proton/H⁻ linac
 - Achieved 1.01 GeV in a demonstration run
- SNS linac architecture consists of
 - Conventional normal conducting structures to 186 MeV
 - Superconducting structures to 1 GeV
- Normal conducting linac was designed and built by Los Alamos National Laboratory
- DTL system consists of 6-tanks, each powered by 2.5 MW, 402.5 MHz klystron
- CCL system consists of 4 modules, each powered by a 5 MW, 805 MHz klystron; 12 segments form a module



SNS Linear Accelerator



- World's first high-energy superconducting linac for protons
- Cryomodules designed and built by Jefferson Laboratory
- Two cavities geometries, ($\beta_g=0.61$, 0.81) are used to cover broad range in particle velocities



SNS Linear Accelerator



- World's first high-energy superconducting linac for protons
- Cryomodules designed and built by Jefferson Laboratory
- Two cavities geometries, ($\beta_g=0.61$, 0.81) are used to cover broad range in particle velocities
- SCL consists of 81 independently-powered 805 MHz cavities, each driven by a 550 kW klystron, in 23 cryomodules



SNS Linear Accelerator



- World's first high-energy superconducting linac for protons
- Cryomodules designed and built by Jefferson Laboratory
- Two cavities geometries, ($\beta_g=0.61$, 0.81) are used to cover broad range in particle velocities
- SCL consists of 81 independently-powered 805 MHz cavities, each driven by a 550 kW klystron, in 23 cryomodules
- Space is reserved for additional cryomodules to give 1.3 GeV
- He plant supports operation at 4 or 2 degrees K



Linac RF Systems


Champion (FRXC01)

- Designed by Los Alamos Nat. Lab
- All systems 8% duty factor: 1.3 ms, 60 Hz
- 7 DTL Klystrons: 2.5 MW 402.5 MHz
- 4 CCL Klystrons: 5 MW 805 MHz
- 81 SCL Klystrons: 550 kW, 805 MHz
- 14 IGBT-based modulators each providing 1 MW average power
- Digital RF controls with feedback and feedforward
- 2nd largest klystron and modulator installation in the world!



Front-End Commissioning and Performance

- Challenges:
 - High current (38 mA) and duty factor (6% beam duty)
 - Small emittance
 - Chopping system performance
 - Source lifetime
- Ongoing R&D program to develop long-lived ion sources at design parameters; **Welton (FROAB02)**
- Front-end emittance specifications are met at design current
- LEBT and MEBT chopper systems meet risetime and extinction ratio specifications
- Reliability of chopper systems has been a limitation in early operation; **Aleksandrov (TUPAS073)**



Parameter	Baseline Design (Front-End)	Achieved (Ion Source)	Achieved (Front-End)	Routine Operation
Peak Current	38 mA	60	50	17
Pulse Length	1.0 msec	1.25	1.0	0.3-0.5
Repetition Rate	60 Hz	60	60	30
Average Current	1.6 mA	2.5 mA	1.05 mA	70 uA
Emittance (rms,norm)	<0.3 π mm-mrad	0.22	0.29, 0.26	N/A




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



Front-End Commissioning and Performance

- Challenges:
 - High current (38 mA) and duty factor (6% beam duty)
 - Small emittance
 - Chopping system performance
 - Source lifetime
- Ongoing R&D program to develop long-lived ion sources at design parameters; **Welton (FROAB02)**
- Front-end emittance specifications are met at design current
- LEBT and MEBT chopper systems meet risetime and extinction ratio specifications
- Reliability of chopper systems has been a limitation in early operation; **Aleksandrov (TUPAS073)**



Parameter	Baseline Design (Front-End)	Achieved (Ion Source)	Achieved (Front-End)	Routine Operation
Peak Current	38 mA	60	50	17
Pulse Length	1.0 msec	1.25	1.0	0.3-0.5
Repetition Rate	60 Hz	60	60	30
Average Current	1.6 mA	2.5 mA	1.05 mA	70 uA
Emittance (rms,norm)	<0.3 π mm-mrad	0.22	0.29, 0.26	N/A



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



SNS Linac Operation and Performance


Challenges

- Stringent beam loss constraints of 1 Watt/m
 - Requires accurate RF setpoint determination
 - Careful phase-space matching
- Output beam quality, particularly emittance growth
 - Requires careful matching
 - Good stability of phase/amplitude
 - Compensation of heavy beam loading with adaptive feedforward methods
- Evolving SC cavity setpoints
 - Rapid methods to use inherent flexibility of individually powered cavities


Longitudinal Setpoints determined with “Phase Scan Signature Matching” that uses time-of-flight measurements with a model-based algorithm to determine

- input energy
- beam-RF phase and
- RF amplitude

BPM phase diff



BPM phase diff



Cavity phase



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY

PAC 2007, June 25, 2007




Superconducting Linac Operation

Campisi (WEPMS072), Kim (WEPMS076), Stout (MOPAS082)

- Operating at 30 Hz, 2.1 K, 890 MeV, with 75 cavities online of 77 available (one CM has been removed)
- Operating gradients are shown; individual cavity limits are higher
- We are operating ~6 cavities with unusual HOM signals that indicate electron activity
- The inherent flexibility of individually powered cavities is used to “tune-around” an unpowered cavity.
- A rapid method (1 minute) for “fault recovery” is used to rephase the linac in response to RF setpoint changes
- We are constructing an SRF Facility for maintenance, repair and development

Accelerating Gradient (MV/m)



Large fundamental power through HOM coupler



Field probe and/or internal cable (control is difficult at rep. rate >30 Hz)



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY

PAC 2007, June 25, 2007



SNS Linac Performance Specifications

Aleksandrov (TUPAS074, THOAB01)

	Baseline Design	Achieved	Routine Operation
Energy	1000	1010 ✓	890
RMS normalized output emittance (π mm-mrad)	<0.4	0.3, 0.3 ✓ (25 mA, 50 μ s)	
Pulse to pulse jitter	+/- 1.5 MeV	+/- 1.3 MeV ✓	
Average current	1600 μ A	100 μ A	70 μ A
H-/pulse	1.6×10^{14}	1.0×10^{14}	3×10^{13}
RF phase/amplitude stability	1 deg/1%	0.5 deg/ 0.5% ✓	1 deg/1% ✓

- Emittance growth can be controlled
- SNS linac, with independently powered cavities is extremely flexible
- Linac beam dynamics can accommodate unpowered SC cavities with little or no impact on beam quality





OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



Accumulator Ring and Transport Lines

- Designed and built by Brookhaven National Lab
- Accumulates 1-msec long beam pulse by multi-turn charge exchange injection

Circum	248 m
Energy	1 GeV
f_{rev}	1 MHz
Q_x, Q_y	6.23, 6.20
Accum turns	1060
Final Intensity	1.5×10^{14}
Current	26 A



Accumulator Ring Performance

Plum (THXAB03), Cousineau (TUOBKI01)

- Challenges

- High-intensity

- Careful consideration and control of collective effects



- Stringent beam loss constraints < 1 W/m

- Phase-space painting
 - Dual-harmonic RF
 - 2-stage collimation

- Beams from H-stripping inefficiency must be cleanly transported

- World Record proton intensity accumulated and extracted from a storage ring: 0.96×10^{14} protons

- No instabilities with 1000 turns storage!



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



Accumulator Ring Performance

Plum (THXAB03), Cousineau (TUOBKI01)

- Challenges

- High-intensity

- Careful consideration and control of collective effects

- Stringent beam loss constraints < 1 W/m


- Phase-space painting
 - Dual-harmonic RF
 - 2-stage collimation

- Beams from H-stripping inefficiency must be cleanly transported

- World Record proton intensity accumulated and extracted from a storage ring: 0.96×10^{14} protons

- No instabilities with 1000 turns storage!


	Baseline Design	Achieved	Routine Operation
Protons/pulse extracted	1.5×10^{14}	0.96×10^{14}	3×10^{13}
Protons/pulse on target	1.5×10^{14}	5.3×10^{13}	3×10^{13}
Current	26 Amps	17 Amps	5
Turns Accumulated	1060	830	500
Space charge tunes shift	0.15	0.10	0.03



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



Ramp Up to SNS Design Capability




Months since October 1, 2006
OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007




Accelerator Performance Highlights


- SNS began formal operations October 1, 2006
- “Brightest” pulsed spallation neutron source: highest single pulse intensity in routine operation, 6 kJ/pulse
 - 30 kW, 5 Hz, 6.7 μC per pulse
- Routine operation at 60 kW for neutron production
 - 15 Hz, 890 MeV, 4.5 μC /pulse
- Achieved 90 kW in demonstration run
 - 15 Hz, 890 MeV, 6.7 μC /pulse
- We recently passed a readiness review to allow operation up to 2 MW beam power




Ramp-Up Progress to Date: Beam Power on Target




Ramp-Up Progress to Date: Beam Power on Target



Ramp-Up Progress to Date: Beam Power on Target



Ramp-Up Progress to Date: Integrated Beam Power




- **Reliability is a performance limitation we are actively addressing:**
 - Beam chopper systems, modulators, ion source, cryogenic moderator refrigerator, accelerator cooling water system



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



Integrated Beam Power in FY2007: Actual vs. Goal





OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



Beamloss Status at 60 kW Operation

Plum (THXAB03), Zhukov (FRPMN060)

- BLM signals and activation levels (after 30 hr cooldown) from a recent 10 day run at 60 kW (15-25/Mar/07)
- Losses in most of the accelerator are in line with expectations
- We measure higher than desired losses in the Ring Injection region
- We recently re-worked part of the injection dump line to better transport the waste beams from the stripping process; **Holmes (THPAS076), Wang (THPAS078)**



BLM number
OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007




Mercury Target System and Supercritical H₂ Moderator



Target installed on Carriage with phosphor view-screen



Target Change-out Test performed after mercury testing



Carriage

Hg Pump

Target Service Bay

Nuclear News

A PUBLICATION OF THE AMERICAN NUCLEAR SOCIETY February 2007

ROBOTICS AND REMOTE SYSTEMS



SPECIAL SECTION BEGINS ON P. 25

Also in this issue
Perspective: The origin of the EPA's
10 000-year time frame for the
high-level waste repository p. 41



Remote-handling Control Room

Backscattering Spectrometer – BL 2

Dynamics of macromolecules, constrained molecular systems, polymers, biology, chemistry, materials science

Disordered Materials Diffractometer – BL 1b

Liquids, glasses, polymers and biological macromolecular systems, partially ordered complex materials

Wide-Angle Chopper Spectrometer (ARCS) – BL 18

Atomic-level dynamics in materials science, chemistry, condensed matter sciences

High-Resolution Chopper Spectrometer (SEQUOIA) – BL 17

Dynamics of complex fluids, quantum fluids, magnetism, condensed matter, materials science

Ultra-Small Angle Diffractometer – BL 1a

Self assembly of polymers and functional nanomaterials, colloidal systems, microstructures, polymer blends

Vibrational Spectrometer (VISION) – BL 16b

Vibrational dynamics in molecular systems, chemistry

BL 16a

Neutron Spin Echo – BL 15

High-resolution dynamics of slow processes, polymers, and biological macromolecules

Hybrid Spectrometer (HYSPEC) – BL 14B

Atomic-level dynamics in single crystals, magnetism, condensed matter sciences

BL 14a

Fundamental Physics Beam Line – BL 13

Fundamental properties of neutrons

Single-Crystal Diffractometer – BL 12

Atomic-level structures in chemistry, biology, earth science, materials science, condensed matter physics

Macromolecular Diffractometer – BL 11b

Supramolecular systems, molecular magnets, protein crystallography, heterogeneous catalysts, porous materials for separations

Powder Diffractometer (POWGEN) – BL 11a

Atomic-level structures in magnetism, chemistry, materials sciences

Cold Neutron Chopper Spectrometer – BL 5

Condensed matter physics, materials science, chemistry, biology, environmental science

Small-Angle Neutron Scattering Diffractometer – BL 6

Life science, polymer and colloidal systems, materials science, earth and environmental sciences

Engineering Diffractometer (VULCAN) – BL 7

Engineering, materials science, materials processing

High-Pressure Diffractometer – BL 3

Materials science, geology, earth and environmental sciences

Magnetism Reflectometer – BL 4a

Chemistry, magnetism of layered systems and interfaces

Liquids Reflectometer – BL 4b

Interfaces in complex fluids, polymers, chemistry

BL 9

BL 8b

BL 8a

BL 10

LEGEND





Instrument Commissioning and First Science

Backscattering Spectrometer:

Measures diffusive motion of water on TiO_2 (rutile) nanoparticles



Related to environmental science issues in diffusion and transport of water in minerals



Liquids Reflectometer:

Data from poly-electrolyte multilayer in *in-vivo* conditions

Data shows interference fringes between deuterated markers
Related to biomedical aspects of drug delivery (controlled release)




SNS Upgrade Plans

1. **SNS Power Upgrade Project**
 - Doubles beam power capability to 3 MW
 - DOE 20-year plan, mid-term priority
 - Cost range: \$160-183M, project duration 5 years
 - Seeking CD-1 approval now
2. **Second Target Station**
 - Doubles neutron scattering instruments and scientific productivity
 - Lower power and repetition-rate than existing target station
 - In pre-conceptual stage defining science and beam requirements
 - DOE 20-year plan, mid-term priority

Active R&D in many areas:

- Laser-stripping injection: **Danilov (THYKI02)**
- Stripper foil development: **Shaw (MOPAS081)**
- E-p active damping: **Deibele (WEXC01, MOPAS080)**
- Ion Source: **Welton (FROAAB02)**
- LEBT Design: **Han (TUPAS075)**



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007



Conclusion

- The SNS is now an operating facility
- We're making rapid progress toward full design capability
- We are 8 months into an expected 3-year performance ramp
- We are on-track with our ramp-up plans
- SNS is open for business: initial user program begins this summer, expect full user program the following year
- Science results from SNS instruments are emerging



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
PAC 2007, June 25, 2007

